



LISTING INFORMATION OF  
**KLH Massivholz GmbH – Massivholzplatten (solid wood slabs)**  
**CLT**

SPEC ID: 36204

KLH Massivholz GmbH  
Gewerbestraße 4

Teufenbach-Katsch, A-8842  
Austria

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

KLH-Massivholzplatten (solid wood slabs) cross laminated timber (CLT) is a wood structural building element for walls, floors (ceilings) and roofs. The CLT panel consists of 3 to 8 layers of Austrian Spruce lumber boards stacked crosswise (layers at 90°) and glued on their wide faces. The CLT panel is offered in a maximum length of 54 ft 1-5/8 in. (16.5 m); widths of 7 ft 10-½ in. (2.40m), 8 ft 2-7/16 in. (2.50m), 8 ft 11-½ in. (2.73m) and 9 ft 8-5/32 in. (2.95 m); maximum thickness of 1 ft 17/32 in. (0.32 m).

**MATERIAL RATINGS**

Test Standard	Test Type	Rating
ANSI/APA PRG 320	Performance Rated CLT	CV3 – Custom Layup Combinations

**For Use in the U.S.**

Grade	Major Strength Direction (psi)						Minor Strength Direction (psi)					
	F <sub>b,0</sub>	E <sub>0</sub> (10 <sup>6</sup> )	F <sub>t,0</sub>	F <sub>c,0</sub>	F <sub>v,0</sub>	F <sub>s,0</sub>	F <sub>b,90</sub>	E <sub>90</sub> (10 <sup>6</sup> )	F <sub>t,90</sub>	F <sub>c,90</sub>	F <sub>v,90</sub>	F <sub>s,90</sub>
CV3M1	975	1.6	550	1,450	175	55	975	1.6	550	1,450	175	55

Tabulated values are allowable design values and not permitted to be increased for the lumber size adjustment factor in accordance with the NDS. The design values shall be used in conjunction with the section properties provided by KLH based on the actual layup used in manufacturing the CLT panel.

**For Use in Canada**

Grade	Major Strength Direction (MPa)						Minor Strength Direction (MPa)					
	F <sub>b,0</sub>	E <sub>0</sub>	F <sub>t,0</sub>	F <sub>c,0</sub>	F <sub>v,0</sub>	F <sub>s,0</sub>	F <sub>b,90</sub>	E <sub>90</sub>	F <sub>t,90</sub>	F <sub>c,90</sub>	F <sub>v,90</sub>	F <sub>s,90</sub>
CV3M1	10.8	11,000	5.5	15.0	1.8	0.60	10.8	11,000	5.5	15.0	1.8	0.60

Tabulated values are Limit States design values and not permitted to be increased for the lumber size adjustment factor in accordance with the CSA O86. The design values shall be used in conjunction with the section properties provided by KLH based on the actual layup used in manufacturing the CLT panel.

Attribute	Value
Criteria	ANSI/APA PRG 320 (2012)
CSI Code	06 17 00 Shop-Fabricated Structural Wood
Intertek Services	Certification
Listed or Inspected	LISTED
Listing Section	BUILDING PANELS
Report Number	G103136174
Spec ID	36204