


TIPI DI PANNELLI STANDARD

PER USO PARETE
strato esterno orientato in direzione
dell'asse trasversale dei pannelli

Tipo di lastra			Composizione lastra / Spessore lamelle (mm)					
KLH	60 mm	3s DT	20	20	20			
KLH	70 mm	3s DT	20	30	20			
KLH	80 mm	3s DT	30	20	30			
KLH	90 mm	3s DT	30	30	30			
KLH	100 mm	3s DT	30	40	30			
KLH	110 mm	3s DT	40	30	40			
KLH	120 mm	3s DT	40	40	40			
KLH	100 mm	5s DT	20	20	20	20	20	
KLH	110 mm	5s DT	20	20	30	20	20	
KLH	120 mm	5s DT	30	20	20	20	30	
KLH	130 mm	5s DT	30	20	30	20	30	
KLH	140 mm	5s DT	30	20	40	20	30	
KLH	150 mm	5s DT	30	30	30	30	30	
KLH	160 mm	5s DT	40	20	40	20	40	



PER USO SOLAIO E TETTO
strato esterno orientato in direzione
dell'asse longitudinale dei pannelli

KLH	60 mm	3s DL	20	20	20				
KLH	70 mm	3s DL	20	30	20				
KLH	80 mm	3s DL	30	20	30				
KLH	90 mm	3s DL	30	30	30				
KLH	100 mm	3s DL	40	20	40				
KLH	110 mm	3s DL	40	30	40				
KLH	120 mm	3s DL	40	40	40				
KLH	100 mm	5s DL	20	20	20	20	20		
KLH	110 mm	5s DL	20	20	30	20	20		
KLH	120 mm	5s DL	30	20	20	20	30		
KLH	130 mm	5s DL	30	20	30	20	30		
KLH	140 mm	5s DL	40	20	20	20	40		
KLH	150 mm	5s DL	40	20	30	20	40		
KLH	160 mm	5s DL	40	20	40	20	40		
KLH	170 mm	5s DL	40	30	30	30	40		
KLH	180 mm	5s DL	40	30	40	30	40		
KLH	190 mm	5s DL	40	40	30	40	40		
KLH	200 mm	5s DL	40	40	40	40	40		
KLH	160 mm	5ss DL	30+30	40	30+30				
KLH	180 mm	7s DL	20	40	20	20	20	40	20
KLH	200 mm	7s DL	20	40	20	40	20	40	20
KLH	220 mm	7s DL	30	40	30	20	30	40	30
KLH	240 mm	7s DL	30	40	30	40	30	40	30
KLH	180 mm	7ss DL	30+30	20	20	20	30+30		
KLH	200 mm	7ss DL	30+30	20	40	20	30+30		
KLH	220 mm	7ss DL	40+40	20	20	20	40+40		
KLH	240 mm	7ss DL	40+40	20	40	20	40+40		
KLH	260 mm	7ss DL	40+40	30	40	30	40+40		
KLH	280 mm	7ss DL	40+40	40	40	40	40+40		
KLH	300 mm	8ss DL	40+40	30	40+40	30	40+40		
KLH	320 mm	8ss DL	40+40	40	40+40	40	40+40		

