



MADE FOR BUILDING
BUILT FOR LIVING

Declaration of Conformity

No.: DOC_KLH_K_2022_v01

1. Unique identification code of the product type:

KLH® - CLT

2. Intended use:

Solid wood slab elements to be used as structural elements in buildings.

3. Name, registered trade name or registered trademark and contact address of the manufacturer:

**KLH Massivholz GmbH
8842 Teufenbach-Katsch, Gewerbestraße 4
Austria**

4. Authorised representative:

**KLH Massivholz GmbH
8842 Teufenbach-Katsch, Gewerbestraße 4
Austria**

5. System of assessment and verification of constancy of performance:

System 1

6. UK Assessment Document:

UKAD 130005-00-0304

UK Technical Assessment:

UKTA-0836-22/0028 of 16/02/2022

Technical assessment body:

BBA – British Board of Agrément

Notified body:

BBA – British Board of Agrément No 0836

7. Declared properties:

| Product dimensions | |
|---|--------------|
| Widths to | 2 980 mm |
| Lengths to | 16 500 mm |
| Thicknesses from | 60 to 360 mm |
| The actual product dimensions can be obtained from the accompanying documents | |

KLH MASSIVHOLZ GMBH

A-8842 Teufenbach-Katsch | Gewerbestraße 4 | Tel +43 (0)3588 8835 0 | Fax +43 (0)3588 8835 415 | office@klh.at | www.klh.at



MADE FOR BUILDING
BUILT FOR LIVING

| Essential Characteristics | Performance |
|---|---------------------------|
| 1. Mechanical resistance and stability | |
| Plate actions | |
| Modulus of elasticity parallel to the grain of the boards $E_{0,mean}$ perpendicular to the grain of the boards $E_{90,mean}$ | 12 000 MPa 450 MPa |
| Shear modulus parallel to the grain of the boards $G_{0,mean}$ perpendicular to the grain of the boards, rolling shear modulus $G_{90,mean}$ | 690 MPa 50 MPa |
| Bending strength parallel to the grain of the boards $f_{m,k}$ | 24 MPa |
| Tensile strength perpendicular to the grain of the boards $f_{t,90,k}$ | 0,12 MPa |
| Compressive strength perpendicular to the grain of the boards $f_{c,90,k}$ | 2,7 MPa |
| Shear strength parallel to the grain of the boards $f_{v,k}$ perpendicular to the grain of the boards (rolling shear strength) $f_{v,R,k}$ | 2,7 MPa 1,2 MPa |
| Membrane actions | |
| Modulus of elasticity parallel to the grain of the boards $E_{0,mean}$ | 12 000 MPa |
| Shear modulus parallel to the grain of the boards $G_{0,mean}$ | 500 MPa |
| Bending strength parallel to the grain of the boards $f_{m,k}$ | 24 MPa |
| Tensile strength parallel to the grain of the boards $f_{t,0,k}$ | 16,5 MPa |
| Compressive strength concentrated, parallel to the grain of the boards $f_{c,0,k}$ | 24 MPa |
| Shear strength regardless of loading direction, per glue line $f_{v,k,k}$ (Shear flow) parallel to the grain of the boards $f_{v,k}$ (Shear stress) | 90 N/mm 3,9 to 8,4 MPa |

| Essential Characteristics | Performance |
|--|---|
| Other mechanical actions | |
| Embedment strength | According to EN 1995-1-1 |
| Creep and duration of the load | k_{mod} and k_{def} according to EN 1995-1-1 for glued laminated timber |
| Dimensional stability as tolerances based on EN 336 for thickness and width | For elements with a length $> 1\text{ m} \pm 2\text{ mm}$ related to standard cutting and wood moisture content 12 % |
| Dimensional stability as wood moisture content after production | $u = 12 \pm 2\%$ |
| Coefficient of thermal expansion according to EN 1995-1-1 | $a = 5 \times 10^{-6}/K$ |
| In-service environment as service classes according to EN 1995-1-1 | 1 and 2 |
| Bond integrity according to UKAD 130005-00-0304 Adhesives used for surface bonding and finger jointing | Passed According to EN 15425 |
| Glue line integrity as delamination test according to EN 14080, annex C, method B | Delamination fulfilled |

KLH MASSIVHOLZ GMBH

A-8842 Teufenbach-Katsch | Gewerbestraße 4 | Tel +43 (0)3588 8835 0 | Fax +43 (0)3588 8835 415 | office@klh.at | www.klh.at



MADE FOR BUILDING
BUILT FOR LIVING

| Essential Characteristics | Performance |
|--|---|
| 2. Safety in case of fire | |
| Reaction to fire | D-s2, d0 |
| Resistance to fire | Parameters for fire design according to annex 5, table 5 of UKTA-0836-22/0028 Fire resistance duration from REI 30 to REI 240 depending on the panel structure or possible fire protection claddings |
| 3. Hygiene, health and environment | |
| Content, emission and/or release of hazardous substances as formaldehyde emissions | Formaldehyde emission class E1 according to EN 14080, formaldehyde free adhesive |
| Other hazardous substances | NPD |
| Water vapour permeability as water vapour diffusion resistance factor μ (including joints) according to EN ISO 12572 | $\mu = 300$ (dry) to 46 (wet) |
| 4. Safety and accessibility in use | |
| Impact resistance with a soft body | Fulfilled |
| 5. Protection against noise | |
| Airborne sound insulation according to EN 10140-2 | UKTA-0836-22/0028, annex 6 |
| Impact sound insulation according to EN 10140-3 | UKTA-0836-22/0028, annex 6 |
| 6. Energy economy and heat retention | |
| Thermal conductivity according to EN ISO 10456 | $\lambda = 0,12$ W/(m K) |
| Air permeability according to EN 12114 | Class 4 (tight) according to EN 12207 |
| Thermal inertia as specific heat capacity c_p according to EN ISO 10456 | $c_p = 1\ 600$ J/(kg K) |

The performance of the product is in accordance with/conforms to the declared performance. This declaration of conformity is issued under the sole responsibility of the manufacturer identified under item 3 above.

Signed for and on behalf of the manufacturer by:



KLH MASSIVHOLZ GMBH
 8842 Teufenbach-Katsch | Gewerbestraße 4
 Tel +43 (0)3588 8835 | Fax +43 (0)3588 8835 415
 office@klh.at | www.klh.at

Mag. Marco Huter, Managing Director

Ing. Johann Hohegger M.Sc., Managing Director

Teufenbach-Katsch, 29.11.2022



MADE FOR BUILDING
BUILT FOR LIVING

Declaration of Conformity

No.: DOC_KLH_W_2022_v01

1. Unique identification code of the product type:

KLH® - CLT

2. Intended use:

Solid wood slab elements to be used as structural elements in buildings.

3. Name, registered trade name or registered trademark and contact address of the manufacturer:

**KLH Massivholz GmbH
8842 Teufenbach-Katsch, Gewerbstraße 4
Austria**

4. Authorised representative:

**KLH Massivholz Wiesenau GmbH
9462 Bad St. Leonhard, Wiesenau 2
Austria**

5. System of assessment and verification of constancy of performance:

System 1

6. UK Assessment Document:
UK Technical Assessment:
Technical assessment body:
Notified body:

**UKAD 130005-00-0304
UKTA-0836-22/0028 of 16/02/2022
BBA – British Board of Agrément
BBA – British Board of Agrément No 0836**

7. Declared properties:

| Product dimensions | |
|---|--------------|
| Widths to | 3 500 mm |
| Lengths to | 16 500 mm |
| Thicknesses from | 60 to 360 mm |
| The actual product dimensions can be obtained from the accompanying documents | |

KLH MASSIVHOLZ WIESENAU GMBH

A-9462 Bad St. Leonhard | Wiesenau 2 | Tel +43 (0)3588 8835 0 | Fax +43 (0)3588 8835 415 | office@klh.at | www.klh.at



MADE FOR BUILDING
BUILT FOR LIVING

| Essential Characteristics | Performance |
|---|---------------------------|
| 1. Mechanical resistance and stability | |
| Plate actions | |
| Modulus of elasticity parallel to the grain of the boards $E_{0,mean}$ perpendicular to the grain of the boards $E_{90,mean}$ | 12 000 MPa 450 MPa |
| Shear modulus parallel to the grain of the boards $G_{0,mean}$ perpendicular to the grain of the boards, rolling shear modulus $G_{90,mean}$ | 690 MPa 50 MPa |
| Bending strength parallel to the grain of the boards $f_{m,k}$ | 24 MPa |
| Tensile strength perpendicular to the grain of the boards $f_{t,90,k}$ | 0,12 MPa |
| Compressive strength perpendicular to the grain of the boards $f_{c,90,k}$ | 2,7 MPa |
| Shear strength parallel to the grain of the boards $f_{v,k}$ perpendicular to the grain of the boards (rolling shear strength) $f_{v,R,k}$ | 2,7 MPa 1,2 MPa |
| Membrane actions | |
| Modulus of elasticity parallel to the grain of the boards $E_{0,mean}$ | 12 000 MPa |
| Shear modulus parallel to the grain of the boards $G_{0,mean}$ | 500 MPa |
| Bending strength parallel to the grain of the boards $f_{m,k}$ | 24 MPa |
| Tensile strength parallel to the grain of the boards $f_{t,0,k}$ | 16,5 MPa |
| Compressive strength concentrated, parallel to the grain of the boards $f_{c,0,k}$ | 24 MPa |
| Shear strength regardless of loading direction, per glue line $f_{v,k,k}$ (Shear flow) parallel to the grain of the boards $f_{v,k}$ (Shear stress) | 90 N/mm 3,9 to 8,4 MPa |

| Essential Characteristics | Performance |
|--|---|
| Other mechanical actions | |
| Embedment strength | According to EN 1995-1-1 |
| Creep and duration of the load | k_{mod} and k_{def} according to EN 1995-1-1 for glued laminated timber |
| Dimensional stability as tolerances based on EN 336 for thickness and width | For elements with a length $> 1\text{ m} \pm 2\text{ mm}$ related to standard cutting and wood moisture content 12 % |
| Dimensional stability as wood moisture content after production | $u = 12 \pm 2\%$ |
| Coefficient of thermal expansion according to EN 1995-1-1 | $a = 5 \times 10^{-6}/K$ |
| In-service environment as service classes according to EN 1995-1-1 | 1 and 2 |
| Bond integrity according to UKAD 130005-00-0304 Adhesives used for surface bonding and finger jointing Glue line integrity as delamination test according to EN 14080, annex C, method B | Passed According to EN 15425 Delamination fulfilled |

KLH MASSIVHOLZ WIESENAU GMBH

A-9462 Bad St. Leonhard | Wiesenau 2 | Tel +43 (0)3588 8835 0 | Fax +43 (0)3588 8835 415 | office@klh.at | www.klh.at



MADE FOR BUILDING
BUILT FOR LIVING

| Essential Characteristics | Performance |
|--|---|
| 2. Safety in case of fire | |
| Reaction to fire | D-s2, d0 |
| Resistance to fire | Parameters for fire design according to annex 5, table 5 of UKTA-0836-22/0028 Fire resistance duration from REI 30 to REI 240 depending on the panel structure or possible fire protection claddings |
| 3. Hygiene, health and environment | |
| Content, emission and/or release of hazardous substances as formaldehyde emissions | Formaldehyde emission class E1 according to EN 14080, formaldehyde free adhesive |
| Other hazardous substances | NPD |
| Water vapour permeability as water vapour diffusion resistance factor μ (including joints) according to EN ISO 12572 | $\mu = 300$ (dry) to 46 (wet) |
| 4. Safety and accessibility in use | |
| Impact resistance with a soft body | Fulfilled |
| 5. Protection against noise | |
| Airborne sound insulation according to EN 10140-2 | UKTA-0836-22/0028, annex 6 |
| Impact sound insulation according to EN 10140-3 | UKTA-0836-22/0028, annex 6 |
| 6. Energy economy and heat retention | |
| Thermal conductivity according to EN ISO 10456 | $\lambda = 0,12$ W/(m K) |
| Air permeability according to EN 12114 | Class 4 (tight) according to EN 12207 |
| Thermal inertia as specific heat capacity c_p according to EN ISO 10456 | $c_p = 1\ 600$ J/(kg K) |

The performance of the product is in accordance with/conforms to the declared performance. This declaration of conformity is issued under the sole responsibility of the manufacturer identified under item 3 above.

Signed for and on behalf of the manufacturer by:



KLH MASSIVHOLZ WIESENAU GMBH
9400 Wieselburg | Schlemmtratten 7
Tel +43 (0)4350 3810 0 | Fax +43 (0)4350 3810 603
office@klh.at | www.klh.at

Mag. Marco Huter, Managing Director

Ing. Johann Hochegger M.Sc., Managing Director

Bad St. Leonhard, 29.11.2022

KLH MASSIVHOLZ WIESENAU GMBH

A-9462 Bad St. Leonhard | Wiesenau 2 | Tel +43 (0)3588 8835 0 | Fax +43 (0)3588 8835 415 | office@klh.at | www.klh.at